

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> The substrate to which EzPanel Primer is to be applied must be installed in strict accordance with the manufacture's specifications and recommended installation procedures. For concrete/masonry substrates the suppliers required curing time must be allowed after installation to ensure the joints in the substrate have completed cured, shrunk, and stabilized. All solid concrete substrates must be fully cured and dry. New concrete must be at least 21 days old prior to the application of any render product. <p>Surface imperfection such as blowholes, large cracks and spalling must be patched and levelled to the required tolerances and flatness with Specialized render materials before this product is applied. All nibs, protrusions and excess mortar on the surface of the bricks or irregularities in the slab must be ground off prior to rendering.</p> <p>All surfaces must be clean and free of debris, dirt and dust, efflorescence, grease, oils, curing agents, cleaning solutions, mould and algae or any other contaminants that may affect adhesion. Deeply contaminated substrates must be abraded to provide a clean sound surface. All loose or damaged material must be removed by water blasting, captive shot blasting, or mechanical wire brushing and then washed down before rendering commences.</p> <p>Painted or glossy surfaces such as power floated concrete must be specially primed, acid etched or mechanically abraded prior to the application of any render.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> EzPanel Primer can be applied with a pump up sprayer, a short nap paint rollet or paint brush in a crosswise fashion in order to give the surface an even coat. Further applications can only be done after the first coat has thoroughly dried. Plaster can be applied as soon as the sealer has dried. <p>For full system details refer to the Specialized installation guide.</p>

Health And Safety			
MSDS Number	DLX004014	Using Safety Precautions	For detailed information refer to product label and the current Material Safety Data Sheet available through Specialized Construction Products Sales and Customer Service Offices.
MSDS Link	https://go.lupinsys.com/duluxgroup/harms/pm/61c24fcfb75e02142538cc18f38b1d49-published/attachment/nz-sds.pdf		
Protective Equipment	Wear safety shoes, overalls, gloves, safety glasses, dust mask.	Storage	Keep out of reach of children. Store for no longer than 6 in a dry, well-ventilated area and off the floor. Product must be protected from the weather and from mechanical damage. Store away from foodstuffs.
Disposal	Check with your local council first.	Handling	Avoid eye and skin contact.
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
<p>Ensure all surface preparation instruction are followed.</p> <p>Apply EzPanel Primer only when the temperature is above 10°C.</p> <p>EzPanel Primer is not waterproof material nor is suitable for use under conditions where continuous water is present.</p>

Transport And Storage			
Pack A	19TX5000	Shipment Name	Not dangerous goods. No special transport requirements.
Size	Weight		
1L	1.01kg		
5L	5.07kg		
20L	20.28kg		
Flash Point	N/A	UN Number	N/A
Dangerous Goods Class	N/A	Package Group	N/A

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118